

*** PCB SPECIFICATION FOR CIRCUIT BOARD MANUFACTURING ***

PRODUCT OWNER : Energy Micro AS
DOCUMENT/BOARD : PCB9003 REV. A01
DATE : 2012-03-20
REVISION : A01

PREPARED BY : Ole Jacob Bryhni Frostad
BOARDS pr PANEL: 8 (2 x 4)
PANEL SIZE : 250.0 x 290.0 mm
BOARD SIZE : 110.0 x 60.0 mm
BOARD THICKNESS: 1.6 mm +/- 10 %
NO OF LAYERS : 2
MATERIAL(S) : Glass Epoxy FR-4, NEMA Class 2, UL 94V-0, Tg min 140 C
Materials in compliance with the RoHS and WEEE directives
MARKINGS: Logo, Week/Year, UL
(Avoid areas reserved for DataMatrix, Barcodes or Lables)
QUALITY REQ. : IPC-A-600 (current revisions) Class 2, and IPC specifications
referred to by IPC-A-600
GENERAL REQ. : If applicable, the following requirements are valid:
- If Build-Up (Stack-Up) is specified, follow Build-Up,
otherwise use (board manufacturer) standard Build-Up.
- Copper balancing may be applied on break-away-tabs,
or otherwise outside board outline(s), but must have
a minimum 1.5 mm clearance to possible fiducials.
- Break-away areas may be used for patterns, holes etc
by manufacturer for QA purposes.
- Inner radius (contour) 1.2 mm, unless stated otherwise.
- Manufacturer may plug tented via holes to improve yield.
COPPER THK. : Cu thickness outer layers: 35 um (1.0 Oz)
COPPER PASSIV. : ENIG to meet IPC-4552 requirements, except Nickel thickness
must be minimum 4 um. (Electroless Nickel/Immersion Gold)
RESIST MASK : Photo Polymer Wet film (Green)
to IPC-SM-840 Class T requirements (current revision)
VIA HOLES : TENTED (OVERPRINTED, NOT PLUGGED)
UNLESS OPTIONALLY: EXPLICIT OTHER VIA TREATMENT REQUESTED
LEGEND COLOUR : WHITE
LEGEND LAYER(S): PRIMARY SIDE (TOP)
NOMINAL VALUES for Width, Spacing and VIA Diameter:
Cu TRACK(TRACE): Minimum conductor width : 0.10 mm (4 mils)
Cu SPACING : Minimum conductor spacing: 0.10 mm (4 mils)
MINIMUM VIA : Minimum via pad diameter : 0.66 mm (26 mils)
Min via hole (SEE HOLE INFORMATION FURTHER DOWN)
Min via hole may have more than one pad diameter.

(SPECIFICATION CONTINUED ON NEXT PAGE)

TEST : 100% Electrical Test 2(2)
Optical test, AOI (with automatic scanner)
Visual inspection
(Generate netlist from Gerber/Drill files)
The manufacturer must place text or logos on the secondary/bottom side.

NC DRILL - HOLE INFORMATION:

WARNING: Drill dimensions must be taken from the Excellon (.exc) file(s).
NON-PLATED holes may have a small center marker in the Gerber files.
Under no circumstance must these Gerber flashes be mistaken for the
hole drill dimensions!

The drill file may contain slots. See drill information below.
The Gerber file mb9003.gex may also contain slot information.
Dimensions for the finished board (after plating).
Tolerances +/- 0.1 mm, unless specified otherwise below.
Via Holes +0.1 mm/-Via Size, unless specified otherwise below.

PLATED HOLES:

T01 VH DIA = 0.25 mm QTY = 32 (VIA-HOLES)
T02 VH DIA = 0.3 mm QTY = 368 (VIA-HOLES)
T03 PTH DIA = 1.0 mm QTY = 80

NON-PLATED HOLES:

T04 NP DIA = 0.5 mm QTY = 240
T05 NP DIA = 2.0 mm QTY = 40
T06 NP DIA = 3.0 mm QTY = 32

Contec Electronics AS * ECAD Center * Norway
email: post@contecel.com URL: www.contecel.com
Phone: +47 6677 5340 or +47 472 55 462 Fax: +47 6677 5341

+++ YOUR CIRCUIT BOARD DESIGN PARTNER +++
----->