

User Registration

Register today to create your account on Silabs.com. Your personalized profile allows you to receive technical document updates, new product announcements, “how-to” and design documents, product change notices (PCN) and other valuable content available only to registered users. <http://www.silabs.com/profile>

Bulletin Date: 7/3/2014		Bulletin Effective Date: 7/3/2014	
Title: EFM32G Datasheet Revision Notification			
Originator: Ted Batey		Phone: 512-532-5279	Dept: Marketing
Customer Contact: Kathy Haggar		Phone: 512-532-5261	Dept: Sales
Bulletin Details			
Description: Silicon Labs is pleased to announce that version 1.80 of the EFM32G (Gecko family) datasheets and version 1.10 of the EFM32G reference manual are now available. The affected datasheets are: EFM32G200, EFM32G210, EFM32G222, EFM32G230, EFM32G232, EFM32G280, EFM32G290, EFM32G840, EFM32G842, EFM32G880, EFM32G890. The affected reference manual is: EFM32G-RM. The datasheet revision includes a number of key changes to existing Min/Max/Typ values that more accurately reflect the performance of the part. These changes are summarized in Table 1 at the end of this document. In addition, Table 3.12 HFRCO has a new Footnote 5, ensuring frequency bands above 7MHz will always have some overlap across supply voltage and temperature. In addition, new min/max data has been added and other minor updates have been made as follows: • Updated Current Consumption information • Updated Power Management information • Updated GPIO information • Updated LFXO information • Updated HFXO information • Updated HFRCO information and figures • Updated ULFRCO information • Updated ACMP information See Table 1 at the end of this document for additional details. The reference manual has also been changed to reflect the updated operating voltage range and current consumption information.			
Reason: Updated specifications based on the results of additional silicon characterization. There are no physical or software changes to the devices.			

Product Identification:

Affected Part Numbers	Affected Part Numbers	Affected Part Numbers
EFM32G200F16-QFN32	EFM32G232F32-QFP64	EFM32G840F32-QFN64
EFM32G200F32-QFN32	EFM32G232F64-QFP64	EFM32G840F64-QFN64
EFM32G200F64-QFN32	EFM32G232F128-QFP64	EFM32G840F128-QFN64
EFM32G210F128-QFN32	EFM32G280F32-QFP100	EFM32G842F32-QFP64
EFM32G222F32-QFP48	EFM32G280F64-QFP100	EFM32G842F64-QFP64
EFM32G222F64-QFP48	EFM32G280F128-QFP100	EFM32G842F128-QFP64
EFM32G222F128-QFP48	EFM32G290F32-BGA112	EFM32G880F32-QFP100
EFM32G230F32-QFN64	EFM32G290F64-BGA112	EFM32G880F64-QFP100
EFM32G230F64-QFN64	EFM32G290F128-BGA112	EFM32G880F128-QFP100
EFM32G230F128-QFN64		EFM32G890F32-BGA112
		EFM32G890F64-BGA112
		EFM32G890F128-BGA112

This change is considered a minor change which does not affect form, fit, function, quality, or reliability. The information is being provided as a customer courtesy.

Please contact your local Silicon Laboratories sales representative with any questions about this notification. A list of Silicon Laboratories sales representatives may be found at www.silabs.com

Customer Actions Needed:

None. Please see your Silicon Labs sales representatives if you have questions. A list of Silicon Labs sales representatives is available at www.silabs.com

Table 1: EFM32Gxxx Datasheet Rev 1.80 - Summary of Key Changes

Table*	Symbol	Parameter	Condition	Datasheet Rev 1.71			Datasheet Rev 1.80			Unit
				Min	Typ	Max	Min	Typ	Max	
3.2 General Operating Conditions	V _{DDOP}	Operating Supply Voltage		1.85		3.8	1.98		3.8	V
3.6 Power Management	V _{BODextthr}	BOD threshold, falling external supply		1.82		1.85	1.74		1.96	V
3.7 Flash	V _{FLASH}	Flash erase/write supply voltage		1.8		3.8	1.98		3.8	V
3.8 GPIO	V _{IOOH}	Output high voltage	Sourcing 6 mA, V _{DD} = 1.98V	0.75V _{DD}			0.75V _{DD}			V
			Sourcing 6 mA, V _{DD} = 3.0V	0.95V _{DD}			0.85V _{DD}			V
			Sourcing 20 mA, V _{DD} = 1.98V	0.7V _{DD}			0.6V _{DD}			V
			Sourcing 20 mA, V _{DD} = 3.0V	0.9V _{DD}			0.8V _{DD}			V
	V _{IOOL}	Output low voltage	Sinking 6 mA, V _{DD} = 1.98V			0.25V _{DD}			0.3V _{DD}	V
			Sinking 6 mA, V _{DD} = 3.0V			0.05V _{DD}			0.2V _{DD}	V
			Sinking 20 mA, V _{DD} = 1.98V			0.3V _{DD}			0.35V _{DD}	V
			Sinking 20 mA, V _{DD} = 3.0V			0.1V _{DD}			0.2V _{DD}	V
	I _{IOLEAK}	Input leakage current				±25		±0.1	±100	nA
3.13 ULFRCO	f _{ULFRCO}	Oscillation frequency		0.8		1.5	0.7		1.75	kHz
3.16 ACMP	V _{ACMPOFFSET}	Offset voltage			10			0		mV

* Note: Table numbers may vary by datasheet. Numbers listed refer to EFM32G890.