



# Silicon Labs OpenThread SDK 2.6.1.0 GA

## Simplicity SDK Suite 2024.12.1

### February 5, 2025

Thread is a secure, reliable, scalable, and upgradeable wireless IPv6 mesh networking protocol. It provides low-cost bridging to other IP networks while optimized for low-power / battery-backed operation. The Thread stack is designed specifically for Connected Home applications where IP-based networking is desired, and a variety of application layers may be required.

OpenThread released by Google is an open-source implementation of Thread. Google has released OpenThread to accelerate the development of products for the connected home and commercial buildings. With a narrow platform abstraction layer and a small memory footprint, OpenThread is highly portable. It supports system-on-chip (SoC), network co-processor (NCP), and radio co-processor (RCP) designs.

Silicon Labs has developed an OpenThread-based SDK tailored to work with Silicon Labs hardware. The Silicon Labs OpenThread SDK is a fully tested enhanced version of the GitHub source. It supports a broader range of hardware than does the GitHub version, and includes documentation and example applications not available on GitHub.

These release notes cover SDK version(s):

- 2.6.1.0 GA released on February 5, 2025
- 2.6.0.0 GA released on December 16, 2024

## Compatibility and Use Notices

For information about security updates and notices, see the Security chapter of the Platform Release Notes installed with this SDK or on the TECH DOCS tab on <https://www.silabs.com/developers/thread>. Silicon Labs also strongly recommends that you subscribe to Security Advisories for up-to-date information. For instructions, or if you are new to the Silicon Labs OpenThread SDK, see [Using This Release](#).

### Compatible Compilers:

GCC (The GNU Compiler Collection) version 12.2.1, provided with Simplicity Studio.



#### KEY FEATURES

##### OpenThread

- Thread 1.4 certification compliance for Thread devices (SoC)
- Thread 1.3 certification compliance, and 1.4 Alpha support for OTBR
- OTBR NCP mode support - Alpha
- OTBR RCP mode with MCU host (x917) - Alpha
- KNX IOT API support (delivered in Silabs GitHub)
- xG26 Module support
- TrustZone secure key storage support for Thread / MP SoC projects

##### Multiprotocol

- ZigbeeD and OTBR support on OpenWRT – GA
- DMP BLE + CMP ZB & Matter/OT with Concurrent Listening on MG26 for SoC – GA
- 802.15.4 Unified radio scheduler priority component
- Debian packaging support for MP host applications - Alpha

---

## Contents

1	New Items .....	3
1.1	New Components .....	3
1.2	New Features .....	3
1.3	New APIs .....	4
1.4	New Platform Support .....	4
2	Improvements .....	5
3	Fixed Issues .....	6
4	Known Issues in the Current Release .....	7
5	Deprecated Items .....	8
6	Removed Items .....	9
7	Multiprotocol Gateway and RCP .....	10
7.1	New Items .....	10
7.2	Improvements .....	10
7.3	Fixed Issues .....	10
7.4	Known Issues in the Current Release .....	11
7.5	Deprecated Items .....	11
7.6	Removed Items .....	12
8	Using This Release .....	13
8.1	Installation and Use .....	13
8.2	OpenThread GitHub Repository .....	13
8.3	OpenThread Border Router GitHub Repository .....	13
8.4	Using the Border Router .....	13
8.5	NCP/RCP Support .....	14
8.6	Security Information .....	14
8.7	Support .....	15
8.8	SDK Release and Maintenance Policy .....	15
8.9	Thread Certification .....	15

## 1 New Items

### 1.1 New Components

#### Added in release 2.6.0.0

- `ot_diags` - This component provides diagnostic functionalities for OpenThread. This component will enable the standard OpenThread Factory Diagnostics Module in the project and implement the `diag` command in the OpenThread CLI. See <https://github.com/open-thread/openthread/blob/main/src/core/diags/README.md> for a detailed reference on the diagnostics CLI commands.
- `ot_stack_tcp_stubs` - If this component is installed, TCP/IP implementation will be stubbed out for an FTD/MTD application. Otherwise, the TCP/IP implementation is included by default.

### 1.2 New Features

#### Added in release 2.6.0.0

- The versions of OpenThread and the OpenThread Border Router have been updated. See sections 8.2 and 8.3.
- Libraries and sample applications in this SDK default to Thread 1.4.
- OTBR NCP mode support – Alpha
  - This feature has been created to add support to the OTBR that has an ability to let the host processor sleep, while maintaining connectivity on the Thread mesh network.
  - Keeping the OT Network alive while the host is off/sleeping is accomplished using NCP support.
  - For additional detail see `util/third_party/wpantund/README.md`.
- OTBR RCP mode with MCU host (x917) – Alpha
  - Located in `protocol/openthread/embedded-otbr`.
  - Builds an OpenThread Border Router (OTBR) as MCU host on SoC SiWx917. Supports BRD4338A and BRD4342A for host. Supports MG24 (4187c) RCP.
  - Supported MCU projects are under `./si91x_project`:
    - There is an option to build a simple OpenThread FTD CLI (`openthread-si91x-mcu-host.slcp`) or OpenThread Border Router application (`openthread-si91x-otbr-mcu-host.slcp`).
  - Various OTBR components are under `./si91x_component`.
  - Border router application code is under: `./examples/border_router` and `./examples/cli` (for CLI app).
  - PAL code for SiWx917 and MCU portions of the code are under: `./src/mcu`.
  - To Build:
    - See README for instructions on build and setup.
    - Build scripts are under: `./script`.
    - Build sets up this space (`embedded-otbr`) as an SLC extension for the SiSDK it links to.
    - Also links with WiseConnect SLC extension.
  - Notes:
    - This project has dependencies on WiseConnect, SDK, and openthread code.
    - Requires WiseConnect v3.3.2, which does not work with `sisdk-2024.12` due to freertos component issues. Therefore, `sisdk-2024.12` will contain PoC artifacts of embedded OTBR which will depend on `sisdk-2024.6.2` SDK to build the PoC.
- KNX IOT API support (delivered in Silabs GitHub)
  - This repo contains example platform drivers for Siliabs: <https://github.com/SiliconLabs/KNX-IOT-STACK>.
  - The example platform drivers are intended to present the minimal code necessary to support KNX over OpenThread.
  - The platform drivers are used by the [ot-lightswitch](#) sample apps.
  - To learn more about building and running the sample apps, refer to:
    - [KNX IoT OpenThread Light Switch Demo](#)
- xG26 Module support – Refer to the list of MGM260 modules in the New Platform Support section.
- TrustZone secure key storage support for Thread / MP SoC projects
  - `protocol/openthread/sample-apps/ot-ble-dmp/trustzone/ot-ble-dmp-tz-ns.slcp`
  - `protocol/openthread/sample-apps/ot-ble-dmp/trustzone/ot-ble-dmp-tz.slcp`

## 1.3 New APIs

### Added in release 2.6.0.0

- None.

## 1.4 New Platform Support

### Added in release 2.6.0.0

- New modules
  - MGM260PD32VNA2
  - MGM260PD32VNN2
  - MGM260PD22VNA2
  - MGM260PB32VNA5
  - MGM260PB32VNN5
  - MGM260PB22VNA5
- New radio boards
  - MGM260P-RB4350A
  - MGM260P-RB4351A
- Explorer Kit
  - BRD2709A
  - MGM260P-EK2713A

## 2 Improvements

### **Changed in release 2.6.1.0**

- Increased default stack size for baremetal non-rcp projects to account for observed stack issues with thread joiner operations.

### **Changed in release 2.6.0.0**

- The openthread API includes all changes up to and including the updates described here: [https://openthread.io/reference/api-updates#november\\_18\\_2024](https://openthread.io/reference/api-updates#november_18_2024).
- Added port and pin validation to the otPlatDiagGpioSet, otPlatDiagGpioGet, otPlatDiagGpioSetMode, and otPlatDiagGpioGetMode APIs.
- Upgrade to Mbed TLS v3.6.2.
- For certification inheritance, the Platform Abstraction Layer (PAL) is no longer shipped as a library. Instead, it will always be built from source, giving more control to application developers to take advantage of HW specific features.
- Changed instances of uartdrv\_usart component to iostream\_usart in openthread sample apps.
- TCP/IP support can be included or excluded from certification builds by excluding or including the ot\_stack\_tcp\_stubs component.
- Radio receive sensitivity, RSSI averaging time, and RSSI averaging timeout can now be configured using the new SL\_OPENTHREAD\_RECEIVE\_SENSITIVITY, SL\_OPENTHREAD\_RSSI\_AVERAGING\_TIME, and SL\_OPENTHREAD\_RSSI\_AVERAGING\_TIMEOUT configuration options.
- TrustZone sample applications are now production quality.
- A bootloader and the 'bootloader\_interface' component are now required for detailed crash info. Without these, the crash handler will only print out the reset reason as determined by the EMU/RMU.
- Added workspace to enable trustzone for the OpenThread BLE DMP application.
- The following was added to NCP README to better reflect the actual status of the NCP samples apps. "Note that the NCP design model is not supported or tested, although experimental support is available with the OpenThread stack."
- Updated the description of the ot\_ncp\_source component to make it clear that NCP support is experimental and RCP support is production.
- There is now a new radio\_priorities\_15\_4 component. This component enables dynamic adjustment of active transmit priority using a starting priority and a "step" value. The first try starts at the starting active Tx priority, and every subsequent retry decrements the starting value by the "step" value, effectively increasing the priority.
- OPENTHREAD\_CONFIG\_DIAG\_ENABLE config option has been deprecated. Diagnostic support can be enabled by including the ot\_diags component. Thread certification libraries are built with diagnostic support.

### 3 Fixed Issues

#### Fixed in release 2.6.1.0

ID #	Description
1360675	Fixed failing SRP issue. While adding a service from the SRP client (MTD) to the SRP server (FTD), the SRP registering onto the server outputs an error as shown below from the logs on the FTD:  [W] SrpServer-----: Failed to verify message signature: NotCapable [W] SrpServer-----: Failed to process DNS Additional section: NotCapable [W] SrpServer-----: Send fail response: 5
1390396	Addressed a failing Network Diagnostics test for MTDs in 1.4 certification by enabling the uptime feature OPENTHREAD_CONFIG_UPTIME_ENABLE.
1400642	Fixed a bug in flash driver, where on non-PSA enabled devices some NVM settings were not cleared. Updated the flash abstraction to cycle through and delete all Openthread related keys from the device on Factory Reset.

#### Fixed in release 2.6.0.0

ID #	Description
482915 495241 1295252	Fixed a limitation with the UART driver which could cause characters to be lost on CLI input or output. The issue was resolved by replacing the underlying uartdrv driver with the iostream driver.
1238120	In a multiprotocol RCP environment, certain incoming packets were wrongly interpreted as Zigbee Green Power packets, triggering a random outgoing packet. The issue is fixed by strengthening the Zigbee Green Power packet detection on the RCP.
1289835	Fixed issue with the openthread border router dropping more packets than expected when running within a docker container and under duress.
1295725	Fixed an issue where an SSED could potentially run out of Message buffers during Matter Commissioning.
1295848	Fixed occasional occurrence of duplicate header bytes that were causing rcp resets in busy networks with a lot of traffic over SPI. Also, it is recommended to use a higher spi-bus speed (such as 4Mhz - depending on the network traffic) with a reduced debug logging level to have stable communication between host and rcp. Higher spi speed on OTBR can be set in radio-url as 'spi-speed=<>' argument.
1329286	Removed the "-Werror=unused-parameter" GCC compiler option so that applications that have unused parameters can build.
1355458	Fixed typo where last LQI was mistakenly set to RSSI which would result in an incorrect value in the link metrics enhanced ACK.
1357055	Resolved issue using the openthread certification libraries with MGM240SD22VNA2.
1358944	The ot-ble-dmp sample application is now only supported on parts with at least 768k of flash.
1362028	Removed the check in radio PAL for ongoing ACK transmission before calling RAIL_Idle, as this was causing sleepy devices to miss sleep windows sporadically. When IDLE mode is RAIL_IDLE, the RAIL waits for the radio to finish the ongoing Tx operation before idling. Therefore, this check is unnecessary.
1365554	Fixed issue in which efr32 radio counter interfaces were inaccessible by RCP requests over spinel.
1379694	Fixed issue that would result in a bus fault when full logging is enabled with RTT.

## 4 Known Issues in the Current Release

Issues in bold were added since the previous release. If you have missed a release, recent release notes are available on <https://www.silabs.com/developers/thread> in the Tech Docs tab.

ID #	Description	Workaround
815275	Ability to modify the Radio CCA Modes at compile-time using a configuration option in Simplicity Studio is currently not supported.	Use the SL_OPENTHREAD_RADIO_CCA_MODE configuration option defined in openthread-core-efr32-config.h header file included with your project.
1286531 1286532	CSL/SSED instability.	Adjust settings of CSL related configuration macros.
1356462	In heavy traffic situations an RCP reset can occasionally cause the OTBR to assert.	No known workaround.
1362023	When building a Matter app and adding the Mikroe IOStream USART component, the openthread file, iostream_uart.c, is added to the project, leading to the build errors.	Add a component that provides ot_uart_implementation.
1363723	A corrupted SPI header may occur as a result of an OTBR/RCP communicating with ~30 MTD End Devices, polling at 500ms and sending pings to the OTBR/RCP every minute.	No known workaround.
1377923	In certain situations, when using COEX, the RCP may become unresponsive upon receiving a matter "on off toggle" light command.	Disable COEX.
<b>1399368</b>	<b>The experimental OpenThread NCP sample application may have problems forming a network.</b>	<b>No known workaround.</b>

## 5 Deprecated Items

### Deprecated in release 2.6.0.0

Use of the UARTDRV driver has been deprecated and replaced with the IOSTREAM driver.



## 6 Removed Items

### Removed in release 2.6.1.0

- Removed upgrade rule to change uart component instances for Thread apps.

### Removed in release 2.6.0.0

None.

## 7 Multiprotocol Gateway and RCP

### 7.1 New Items

#### **Added in release 2.6.0.0**

Enabled GA SoC support for BLE DMP with Zigbee + OpenThread CMP with concurrent listening on xG26 parts.

Debian alpha support has been added for zigbeed, OTBR and Z3Gateway applications. Zigbeed and OTBR are provided in DEB package format for the chosen reference platform (Raspberry PI 4) as well. See [Running Zigbee, OpenThread, and Bluetooth Concurrently on a Linux Host with a Multiprotocol Co-Processor](#), for details.

Added Zigbeed support for Tizen-0.1-13.1 for arm32 and aarch64 as well as Android 12 for aarch64. More information on Zigbeed can be found at [docs.silabs.com](https://docs.silabs.com).

Added the new “802.15.4 Unified radio scheduler priority” component. This component is used to configure the radio priorities of a 15.4 stack. The component also requires the new “radio\_priority\_configurator” component. This component allows projects to use the Radio Priority Configurator tool in Simplicity Studio to configure the radio priority levels of the stacks that require it.

### 7.2 Improvements

#### **Changed in release 2.6.1.0**

The Zigbee BLE - DynamicMultiprotocolLightSed sample project can now be built for boards with only one LED if the LED1 component is excluded from the project.

This revision has the following improvements for multi-protocol applications when, for example, running Zigbee or OpenThread for the custom use-case of running one protocol at a time:

1. The `sl_zigbee_af_zll_unset_factory_new()` API has been added to allow applications to unset a Zigbee node from the default factory new state when necessary.
2. A callback, `sl_rail_mux_invalid_rx_channel_detected_cb()`, has been added to Zigbee+OT applications. This callback notifies the application when there has been an attempted RX on two different channels while concurrent listening is not enabled. The application can then implement its own logic to handle this situation.

#### **Changed in release 2.6.0.0**

Application note *Running Zigbee, OpenThread, and Bluetooth Concurrently on a Linux Host with a Multiprotocol Co-Processor* (AN1333) has been moved to [docs.silabs.com](https://docs.silabs.com).

OpenWRT support is now GA quality. OpenWRT support has been added for zigbeed, OTBR and Z3Gateway applications. Zigbeed and OTBR are provided in IPK package format for the reference platform (Raspberry PI 4) as well. See [Running Zigbee, OpenThread, and Bluetooth Concurrently on a Linux Host with a Multiprotocol Co-Processor](#), for details.

### 7.3 Fixed Issues

#### **Fixed in release 2.6.1.0**

ID #	Description
1363050	Zigbee stack initialization no longer activates the radio (or RCP for host stacks) prior to stack APIs being called by the application. This prevents unwanted multi-PAN operation on Channel 11 (the default channel) when using a multi-PAN-capable RCP configuration. (Other ref: 1390724)
1378298	Fixed an issue that caused a crash when entering “keys print” on an DMP Light app with LTO enabled.
1381165	Fixed an issue on Zigbee-NCP + OT-RCP, when disabling PTA would have caused NCP/RCP reset.

**Fixed in release 2.6.0.0**

ID #	Description
1275378	Fixed an issue where calling <code>sl_802154_radio_set_scheduler_priorities()</code> prior to <code>sli_mac_lower_mac_init()</code> could result in a crash.
1300848	Fixed an issue where Z3Gateway in OpenWRT environment couldn't start EZSP communication caused by mismatching termios control characters running on OpenWRT and other environments.
1332330	Fixed an issue where a 15.4+BLE RCP operating in an environment with heavy network traffic could occasionally encounter a race condition that would leave it unable to send messages up to CPCd until rebooting the device.
1337101	Incomplete 15.4 transmit operations (Tx waiting for an ack, Tx an ack in response to a message, etc) are no longer prematurely considered as failed upon radio interruption due to DMP. This allows said operation to be given a chance to be rescheduled after the interruption or permanently failed by RAIL (scheduler status error events).
1337228	In Zigbeed the <code>halCommonGetInt32uMillisecondTick()</code> tick API is now updated to use MONOTONIC clock, so that it does not get affected by the NTP in a host system.
1337295	The DMP CLI command "plugin ble gap print-connections" will now print "No BLE connections" if the connection table is empty, instead of providing no response.
1346785	Fixed a race condition which could cause concurrent listening to be disabled on the 802.15.4 RCP when both protocols were transmitting simultaneously.
1346849	Adding the <code>rail_mux</code> components to a project will now cause it to automatically build with the associated stack library variants.
1365665	Fixed an issue where the host would report receiving a packet with an invalid checksum on end-point 12.

**7.4 Known Issues in the Current Release**

Issues in bold were added since the previous release. If you have missed a release, recent release notes are available on <https://www.silabs.com/developers/simplicity-software-development-kit>.

ID #	Description	Workaround
937562	Bluetoothctl 'advertise on' command fails with <code>rcp-uart-802154-blehci</code> app on Raspberry Pi OS 11.	Use <code>btmgmt</code> app instead of <code>bluetoothctl</code> .
1074205	The CMP RCP does not support two networks on the same PAN id.	Use different PAN ids for each network. Support is planned in a future release.
1122723	In a busy environment, the CLI may become unresponsive in the <code>z3-light_ot-ftd_soc</code> app.	No known workaround.
1209958	The ZB/OT/BLE RCP using concurrent listening on MG24 and MG21 may stop working in endurance test (lasts ~2 hours) with constant and concurrent traffic on all 3 stacks.	Disable concurrent listening in use cases involving constant and concurrent traffic across all 3 protocols.
1221299	Mfglib RSSI readings differ between RCP and NCP.	Will be addressed in a future release.
<b>1392015</b>	<b>RCP applications using parts with &lt;64kB of RAM can run into memory allocation issues. It is recommended to set <code>SL_OPENTHREAD_ENABLE_SERIAL_TASK</code> to 0 to reduce the task memory size which is not required for RCP applications.</b>	<b>Will be addressed in a future release.</b>
<b>1393057</b>	<b>Zigbee-NCP + OT-RCP image currently is not recommended on parts that have 64 kB of RAM.</b>	<b>Will be addressed in a future release.</b>

**7.5 Deprecated Items**

The "Multiprotocol Container" which is currently available on DockerHub ([siliconlabsinc/multiprotocol](https://hub.docker.com/r/siliconlabsinc/multiprotocol)) will be deprecated in an up-coming release. The container will no longer be updated and able to be pulled from DockerHub. The Debian-based packages for `cpcd`, `zigbeed`, and `ot-br-posix`, along with natively generated and compiled projects, will replace the functionality lost with the re-moval of the container.

## 7.6 Removed Items

### Removed in release 2.6.1.0

sl\_sec\_man\_init() has been removed, since it no longer serves a purpose.

### Removed in release 2.6.0.0

None.

## 8 Using This Release

This release contains the following

- Silicon Labs OpenThread stack
- Silicon Labs OpenThread sample applications
- Silicon Labs OpenThread border router

For more information about the OpenThread SDK see [QSG170: Silicon Labs OpenThread QuickStart Guide](#). If you are new to Thread see [UG103.11: Thread Fundamentals](#).

### 8.1 Installation and Use

The OpenThread SDK is part of the Simplicity SDK, the suite of Silicon Labs SDKs. To quickly get started with OpenThread and the Simplicity SDK, start by installing [Simplicity Studio 5](#), which will set up your development environment and walk you through Simplicity SDK installation. Simplicity Studio 5 includes everything needed for IoT product development with Silicon Labs devices, including a resource and project launcher, software configuration tools, full IDE with GNU toolchain, and analysis tools. Installation instructions are provided in the online [Simplicity Studio 5 User's Guide](#).

Alternatively, Simplicity SDK may be installed manually by downloading or cloning the latest from GitHub. See [https://github.com/SiliconLabs/simplicity\\_sdk](https://github.com/SiliconLabs/simplicity_sdk) for more information.

The GSDK default installation location has changed beginning with Simplicity Studio 5.3.

- Windows: C:\Users\\SimplicityStudio\SDKs\simplicity\_sdk
- MacOS: /Users/<NAME>/SimplicityStudio/SDKs/simplicity\_sdk

Documentation specific to the SDK version is installed with the SDK. API references and other information about this release are available on <https://docs.silabs.com/openthread/latest/>. Select your SDK version in the upper right.

### 8.2 OpenThread GitHub Repository

The Silicon Labs OpenThread SDK includes all changes from the OpenThread GitHub repo (<https://github.com/openthread/openthread>) up to and including commit [7f6723ffb](#). An enhanced version of the OpenThread repo can be found in the following Simplicity Studio 5 GSDK location:

```
<GSDK Installation Location>\util\third_party\openthread
```

### 8.3 OpenThread Border Router GitHub Repository

The Silicon Labs OpenThread SDK includes all changes from the OpenThread border router GitHub repo (<https://github.com/openthread/ot-br-posix>) up to and including commit [7d327005e](#). An enhanced version of the OpenThread border router repo can be found in the following Simplicity Studio 5 GSDK location:

```
<GSDK Installation Location>\util\third_party\ot-br-posix
```

### 8.4 Using the Border Router

For ease of use, Silicon Labs recommends the use of a Docker container for your OpenThread border router. Refer to [AN1256: Using the Silicon Labs RCP with the OpenThread Border Router](#) for details on how to set up the correct version of OpenThread border router Docker container. It is available at <https://hub.docker.com/r/siliconlabsinc/openthread-border-router>.

If you are manually installing a border router, using the copies provided with the Silicon Labs OpenThread SDK, refer to [AN1256: Using the Silicon Labs RCP with the OpenThread Border Router](#) for more details.

Although updating the border router environment to a later GitHub version is supported on the OpenThread website, it may make the border router incompatible with the OpenThread RCP stack in the SDK.

## 8.5 NCP/RCP Support

The OpenThread NCP support is included with OpenThread SDK but any use of this support should be considered experimental. The OpenThread RCP is fully implemented and supported.

## 8.6 Security Information

### Secure Vault Integration

When deployed to Secure Vault High devices, sensitive keys are protected using the Secure Vault Key Management functionality. The following table shows the protected keys and their storage protection characteristics.

Wrapped Key	Exportable / Non-Exportable	Notes
Thread Master Key	Exportable	Must be exportable to form the TLVs
PSKc	Exportable	Must be exportable to form the TLVs
Key Encryption Key	Exportable	Must be exportable to form the TLVs
MLE Key	Non-Exportable	
Temporary MLE Key	Non-Exportable	
MAC Previous Key	Non-Exportable	
MAC Current Key	Non-Exportable	
MAC Next Key	Non-Exportable	

Wrapped keys that are marked as “Non-Exportable” can be used but cannot be viewed or shared at runtime.

Wrapped keys that are marked as “Exportable” can be used or shared at runtime but remain encrypted while stored in flash.

For more information on Secure Vault Key Management functionality, see [AN1271: Secure Key Storage](#).

### Security Advisories

To subscribe to Security Advisories, log in to the Silicon Labs customer portal, then select **Account Home**. Click **HOME** to go to the portal home page and then click the **Manage Notifications** tile. Make sure that ‘Software/Security Advisory Notices & Product Change Notices (PCNs)’ is checked, and that you are subscribed at minimum for your platform and protocol. Click **Save** to save any changes.

**Update Preference**

WHAT EMAILS WOULD YOU LIKE TO RECEIVE?

Newsletters

- Community Monthly Newsletter
- Sales Newsletter
- Micrium Newsletter

Product Specific Notifications

- Product Information and Newsletter
- Software/Security Advisory Notices & Product Change Notices (PCNs)
- Technical Document Updates (Release Notes, Data Sheets, etc.)

SELECT THE PRODUCTS TO RECEIVE UPDATES FOR

Select/Unselect All

<input type="checkbox"/> Audio and Radio	<input type="checkbox"/> Power over Ethernet
<input type="checkbox"/> Interface	<input type="checkbox"/> Sensors
<input type="checkbox"/> Isolation	<input type="checkbox"/> TV and Video
<input type="checkbox"/> Modems and DAAs	<input type="checkbox"/> Voice
<input type="checkbox"/> Microcontrollers	<input type="checkbox"/> Wireless
<input type="checkbox"/> 8-bit MCUs <input checked="" type="checkbox"/> 32-bit MCUs	<input type="checkbox"/> Bluetooth Classic <input type="checkbox"/> Bluetooth Low Energy <input checked="" type="checkbox"/> Proprietary <input type="checkbox"/> Wi-Fi <input type="checkbox"/> ZigBee and Thread <input type="checkbox"/> Z-Wave
<input type="checkbox"/> Timing	
<input type="checkbox"/> Clocks	
<input type="checkbox"/> Buffers	
<input type="checkbox"/> Oscillators	
<input type="checkbox"/> CDR and PHY	

## 8.7 Support

Development Kit customers are eligible for training and technical support. Use the [Silicon Laboratories Thread web page](#) to obtain information about all Silicon Labs OpenThread products and services, and to sign up for product support.

You can contact Silicon Laboratories support at <http://www.silabs.com/support>.

## 8.8 SDK Release and Maintenance Policy

For details, see [SDK Release and Maintenance Policy](#).

## 8.9 Thread Certification

This release has been qualified for Thread 1.4.0 for the SoC architectures with Thread Test Harness v62.0 (Member Release). For the Host-RCP architectures, this release has been qualified for Thread 1.3.0 with Thread Test Harness v62.0 (Member Release) with the 1.4.0 qualification currently in alpha release status. For Thread Product certifications tied to this major release and associated patch releases (with no Open-Thread stack updates), Silicon Labs recommends using the above TH version for qualification. Also included with this release is a set of OpenThread stack libraries that may be used for Thread certification by inheritance.

# Simplicity Studio

One-click access to MCU and wireless tools, documentation, software, source code libraries & more. Available for Windows, Mac and Linux!



**IoT Portfolio**  
[www.silabs.com/IoT](http://www.silabs.com/IoT)



**SW/HW**  
[www.silabs.com/simplicity](http://www.silabs.com/simplicity)



**Quality**  
[www.silabs.com/quality](http://www.silabs.com/quality)



**Support & Community**  
[www.silabs.com/community](http://www.silabs.com/community)

## Disclaimer

Silicon Labs intends to provide customers with the latest, accurate, and in-depth documentation of all peripherals and modules available for system and software implementers using or intending to use the Silicon Labs products. Characterization data, available modules and peripherals, memory sizes and memory addresses refer to each specific device, and "Typical" parameters provided can and do vary in different applications. Application examples described herein are for illustrative purposes only. Silicon Labs reserves the right to make changes without further notice to the product information, specifications, and descriptions herein, and does not give warranties as to the accuracy or completeness of the included information. Without prior notification, Silicon Labs may update product firmware during the manufacturing process for security or reliability reasons. Such changes will not alter the specifications or the performance of the product. Silicon Labs shall have no liability for the consequences of use of the information supplied in this document. This document does not imply or expressly grant any license to design or fabricate any integrated circuits. The products are not designed or authorized to be used within any FDA Class III devices, applications for which FDA premarket approval is required or Life Support Systems without the specific written consent of Silicon Labs. A "Life Support System" is any product or system intended to support or sustain life and/or health, which, if it fails, can be reasonably expected to result in significant personal injury or death. Silicon Labs products are not designed or authorized for military applications. Silicon Labs products shall under no circumstances be used in weapons of mass destruction including (but not limited to) nuclear, biological or chemical weapons, or missiles capable of delivering such weapons. Silicon Labs disclaims all express and implied warranties and shall not be responsible or liable for any injuries or damages related to use of a Silicon Labs product in such unauthorized applications.

## Trademark Information

Silicon Laboratories Inc.<sup>®</sup>, Silicon Laboratories<sup>®</sup>, Silicon Labs<sup>®</sup>, SiLabs<sup>®</sup> and the Silicon Labs logo<sup>®</sup>, Bluegiga<sup>®</sup>, Bluegiga Logo<sup>®</sup>, EFM<sup>®</sup>, EFM32<sup>®</sup>, EFR, Ember<sup>®</sup>, Energy Micro, Energy Micro logo and combinations thereof, "the world's most energy friendly microcontrollers", Redpine Signals<sup>®</sup>, WiSeConnect, n-Link, EZLink<sup>®</sup>, EZRadio<sup>®</sup>, EZRadioPRO<sup>®</sup>, Gecko<sup>®</sup>, Gecko OS, Gecko OS Studio, Precision32<sup>®</sup>, Simplicity Studio<sup>®</sup>, Telegesis, the Telegesis Logo<sup>®</sup>, USBXpress<sup>®</sup>, Zentri, the Zentri logo and Zentri DMS, Z-Wave<sup>®</sup>, and others are trademarks or registered trademarks of Silicon Labs. ARM, CORTEX, Cortex-M3 and THUMB are trademarks or registered trademarks of ARM Holdings. Keil is a registered trademark of ARM Limited. Wi-Fi is a registered trademark of the Wi-Fi Alliance. All other products or brand names mentioned herein are trademarks of their respective holders.



Silicon Laboratories Inc.  
400 West Cesar Chavez  
Austin, TX 78701  
USA

[www.silabs.com](http://www.silabs.com)