

<-----
*** PCB SPECIFICATION FOR BARE BOARD MANUFACTURING ***

PRODUCT OWNER : Silicon Labs
DOCUMENT/BOARD : PCB4152x Rev B00
DATE : 2016-02-02
REVISION : B00

PREPARED BY : Ole Jacob Bryhni Frostad
BOARDS pr PANEL: 12 (4 X 3)
PANEL SIZE : 210.2 x 205.4 mm
BOARD SIZE : 30.0 x 45.0 mm
BOARD THICKNESS: 1.6 mm +/- 10 %
NO OF LAYERS : 4
MATERIAL(S) : Glass Epoxy FR-4, NEMA Class 2, UL 94V-0, Tg min 150 C
Materials in compliance with the RoHS and WEEE directives
MARKINGS: Logo, Week/Year, UL (ON SECONDARY SIDE (BOT))
(Avoid areas reserved for DataMatrix, Barcodes or Lables)
QUALITY REQ. : IPC-A-600 (current revisions) Class 2, and IPC specifications
referred to by IPC-A-600
GENERAL REQ. : - Copper must not be added or removed from inside the board outline(s),
without written consent/approval.
If applicable, the following requirements are valid:
- Copper balancing may be applied on break-away-tabs,
or otherwise outside board outline(s), but must have
a minimum 1.5 mm clearance to possible fiducials.
- If Build-Up (Stack-Up) is specified, follow Build-Up,
otherwise use (board manufacturer) standard Build-Up.
- Break-away areas may be used for patterns, holes etc
by manufacturer for QA purposes.
- If V-CUT, use angle 30 +/- 5 degrees.
V-CUT minimum remaining thickness 0.5 +/- 0.1 mm.
Use of V-CUT test pads is allowed.
- Inner radius (contour/outline) 1.2 mm, unless stated otherwise.
COPPER THK. : SEE BUILD-UP
COPPER PASSIV. : ENIG to meet IPC-4552 requirements (current revision)
(Electroless Nickel/Immersion Gold)
RESIST MASK : Solder Mask Color: BLACK (NB! NON-STANDARD)
Photo Polymer Wet film
to IPC-SM-840 Class T requirements (current revision)
Thickness minimum 8 um, maximum 20 um
VIA HOLES : PLUGGED/FILLED, IPC-4761 (current revision) Type IV-b
Plugged and Covered Both Sides, Low CTE Plugging Paste
UNLESS OPTIONALLY: EXPLICIT OTHER VIA TREATMENT REQUESTED
LEGEND/SILKSCR.: WHITE, BOTH SIDES (TOP + BOT)
CONTROLLED IMP : Design has Controlled impedances. FOLLOW BUILD-UP STRICTLY!
Unless explicitly stated otherwise, controlled impedance
has been designed into the board. Use of test strip is
hence normally not required.
NOMINAL VALUES for Width, Spacing and VIA Diameter:
Cu TRACK(TRACE): Minimum conductor width : 0.10 mm (4 mils)
Cu SPACING : Minimum conductor spacing: 0.10 mm (4 mils)
MINIMUM VIA : Minimum via pad diameter : 0.51 mm (20 mils)
Min via hole (SEE HOLE INFORMATION FURTHER DOWN)
Min via hole may have more than one pad diameter.

(SPECIFICATION CONTINUED ON NEXT PAGE)

BUILD UP :

```

L1 ===== 35 um Cu (ca) After plating
////////// C O R E ////////// 300 um
L2 ===== 18 um Cu (0.5 Oz)
- - - P R E P R E G - - - 900 um (ca)
L3 ===== 18 um Cu
////////// C O R E ////////// 300 um
L4 ===== 35 um Cu

```

Prepreg may be adjusted in order to reach correct board thickness

TEST

: 100% Electrical Test
 Optical test, AOI (with automatic scanner)
 Visual inspection
 (Generate netlist from Gerber and Drill files)

Avoid use of 2125 Prepreg

If NB! is used in this specification, it means:
 abbreviation for nota bene!, a Latin expression meaning "note well!"

NC DRILL - HOLE INFORMATION:

WARNING: Drill dimensions must be taken from the Excellon drill file(s) (.DRL), and the drill report file(s) (.DRR).

NON-PLATED holes may have a small center marker in the Gerber files.
 Under no circumstance must these Gerber flashes be mistaken for the hole drill dimensions!

The drill data may contain slots (in a separate file).
 Dimensions for the finished board (after plating).
 Tolerances +/- 0.1 mm, unless specified differently.
 Via Holes +0.05 mm/-Via Size, unless specified differently.

Contec Electronics AS * ECAD Center * Norway
 email: post@contecel.com URL: www.contecel.com
 Phone: +47 6677 5340 or +47 472 55 462 Fax: +47 6677 5341

+++ YOUR CIRCUIT BOARD DESIGN PARTNER +++