

*** PCB SPECIFICATION FOR BARE BOARD MANUFACTURING ***

PRODUCT OWNER : Silicon Labs
DOCUMENT/BOARD : PCB4502 Rev B00
DATE : 2014-10-23
REVISION : B00

PREPARED BY : Ole Jacob Bryhni Frostad
BOARDS pr PANEL: 12 (4 x 3)
PANEL SIZE : 210.2 x 205.4 mm
BOARD SIZE : 30.0 x 41.0 mm
BOARD THICKNESS: 1.6 mm +/- 10 %
NO OF LAYERS : 6
MATERIAL(S) : Glass Epoxy FR-4, NEMA Class 2, UL 94V-0, Tg min 150 C
Materials in compliance with the RoHS and WEEE directives
MARKINGS: Logo, Week/Year, UL (ON SECONDARY SIDE (BOT))
(Avoid areas reserved for DataMatrix, Barcodes or Lables)
QUALITY REQ. : IPC-A-600 (current revisions) Class 2, and IPC specifications
referred to by IPC-A-600
GENERAL REQ. : - Copper must not be added or removed from inside the board outline(s),
without written consent/approval.
If applicable, the following requirements are valid:
- Copper balancing may be applied on break-away-tabs,
or otherwise outside board outline(s), but must have
a minimum 1.5 mm clearance to possible fiducials.
- If Build-Up (Stack-Up) is specified, follow Build-Up,
otherwise use (board manufacturer) standard Build-Up.
- Break-away areas may be used for patterns, holes etc
by manufacturer for QA purposes.
- If V-CUT, use angle 30 +/- 5 degrees.
V-CUT minimum remaining thickness 0.5 +/- 0.1 mm.
Use of V-CUT test pads is allowed.
- Inner radius (contour/outline) 1.2 mm, unless stated otherwise.
COPPER THK. : SEE BUILD-UP
COPPER PASSIV. : ENIG to meet IPC-4552 requirements (Electroless Nickel/Immersion Gold)
RESIST MASK : Solder Mask Color: BLACK (NB! NON-STANDARD)
Photo Polymer Wet film
to IPC-SM-840 Class T requirements (current revision)
Thickness minimum 8 um, maximum 20 um
VIA HOLES : TENTED (OVERPRINTED, NOT PLUGGED) IPC-4761 Type I
THIS BOARD MUST NOT BE PLUGGED!
THESE BOARDS MUST NOT BE PLUGGED
LEGEND/SILKSCR.: WHITE, BOTH SIDES (TOP + BOT)
Separate Silk Top for PCB4502A, PCB4502B, PCB4502C and PCB4502D
All other PCB files are equal for the PCB4502 boards A, B, C and D
CONTROLLED IMP : Design has Controlled impedances. FOLLOW BUILD-UP STRICTLY!
Unless explicitly stated otherwise, controlled impedance
has been designed into the board. Use of test strip is
hence normally not required.
NOMINAL VALUES for Width, Spacing and VIA Diameter:
Cu TRACK(TRACE): Minimum conductor width : 0.10 mm (4 mils)
Cu SPACING : Minimum conductor spacing: 0.0889 mm (3.5 mils)
MINIMUM VIA : Minimum via pad diameter : 0.51 mm (20 mils)
Min via hole (SEE HOLE INFORMATION FURTHER DOWN)
Min via hole may have more than one pad diameter.

(SPECIFICATION CONTINUED ON NEXT PAGE)

BUILD UP :

```

L1 ===== 35 um Cu
  /////////// C O R E /////////// 304 um
L2 ===== 18 um Cu (0.5 Oz)
  - - - - P R E P R E G - - - - 100 um
L3 ===== 18 um Cu
  - - /////////// C O R E /////////// 700 um - - CENTER - -
L4 ===== 18 um Cu
  - - - - P R E P R E G - - - - 100 um
L5 ===== 18 um Cu
  /////////// C O R E /////////// 304 um
L6 ===== 35 um Cu

```

(Approximate Prepreg thicknesses)

Prepreg thickness may be adjusted in order
to reach target board thickness.

TEST : 100% Electrical Test
Optical test, AOI (with automatic scanner)
Visual inspection
(Generate netlist from Gerber and Drill files)

Avoid use of 2125 Prepreg

If NB! is used in this specification, it means:
abbreviation for nota bene!, a Latin expression meaning "note well!"

NC DRILL - HOLE INFORMATION:

WARNING: Drill dimensions must be taken from the Excellon (.exc) file(s).
NON-PLATED holes may have a small center marker in the Gerber files.
Under no circumstance must these Gerber flashes be mistaken for the
hole drill dimensions!

The drill file may contain slots. See drill information below.
The Gerber file mb4502.gex may also contain slot information.
Dimensions for the finished board (after plating).
Tolerances +/- 0.1 mm, unless specified otherwise below.
Via Holes +0.05 mm/-Via Size, unless specified otherwise below.

PLATED HOLES:

```

T01 VH   DIA = 0.25 mm   QTY = 2076 (VIA-HOLES)
T02 VH   DIA = 0.3 mm   QTY = 1728 (VIA-HOLES)
T03 PTH  DIA = 1.5 mm   QTY = 12
T04 PTH  DIA = 1.6 mm   QTY = 48

```

NON-PLATED HOLES:

```

T05 NP   DIA = 1.35 mm   QTY = 48
T06 NP   DIA = 3.0 mm   QTY = 2

```

Contec Electronics AS * ECAD Center * Norway
email: post@contecel.com URL: www.contecel.com
Phone: +47 6677 5340 or +47 472 55 462 Fax: +47 6677 5341

+++ YOUR CIRCUIT BOARD DESIGN PARTNER +++